

It is claimed:

1           1. A bar-shaped lamp comprising:

2           an elongated shaft;

3           a lamp head affixed to one end of said shaft and  
4 provided with a light source; and

5           a reversible elongated foot member receivable in said  
6 shaft at an opposite end of said shaft and having at a first end  
7 of said foot member an elongated spike adapted to be inserted  
8 into the ground and at a second end of said foot member an impact  
9 tool capable of rupturing a vehicle window.

1           2. The bar-shaped lamp defined in claim 1 wherein said

2 light source includes at least one light-emitting diode.

1           3. The bar-shaped lamp defined in claim 2 wherein said

2 light source includes a plurality of light-emitting diodes.

1           4. The bar-shaped lamp defined in claim 3 wherein said

2 spike and said tool are both conical.

1           5. The bar-shaped lamp defined in claim 4 wherein said  
2 spike and said tool have respective apex angles with the apex  
3 angle of said spike being less than the apex angle of said tool.

1           6. The bar-shaped lamp defined in claim 5 wherein said  
2 foot member has a portion between said spike and said tool which  
3 is flush with said shaft and adapted to be inserted into said  
4 shaft.

1           7. The bar-shaped lamp defined in claim 6 wherein  
2 said portion has a friction fit in said shaft.

1           8. The bar-shaped lamp defined in claim 6 wherein said  
2 portion is threaded into said shaft.

1           9. The bar-shaped lamp defined in claim 6, further  
2 comprising a connection replaceable securing said lamp head on  
3 said shaft.

1                   10. The bar-shaped lamp defined in claim 9 wherein  
2       said connection is a threaded connection.

1                   11. The bar-shaped lamp defined in claim 10 wherein  
2       said lamp head comprises a plate, a plurality of light-emitting  
3       diodes mounted on said plate and a spiral contact spring  
4       resiliently engageable with a battery in said shaft.

1                   12. The bar-shaped lamp defined in claim 11, further  
2       comprising a cap adapted to receive said tool and threaded onto  
3       said foot member.

1                   13. The bar-shaped lamp defined in claim 12, further  
2       comprising an elongated light-transmitting body affixed to said  
3       head and illuminatable thereby.

1                   14. The bar-shaped lamp defined in claim 13 wherein  
2       said body is a rod of a light-conducting plastic.

1           15. The bar-shaped lamp defined in claim 14 wherein  
2      said rod is composed of polymethylmethacrylate and is threadedly  
3      connected to said shaft.

1           16. The bar-shaped lamp defined in claim 1 wherein  
2      said shaft comprises a battery holder and a compartment  
3      dimensioned to receive said spike.

1           17. The bar-shaped lamp defined in claim 16, further  
2      comprising a cap adapted to receive said tool and threaded onto  
3      said foot member.

1           18. The bar-shaped lamp defined in claim 17, further  
2      comprising an elongated light-transmitting of an acrylic resin  
3      body affixed to said head and illuminatable thereby.

1           19. The bar-shaped lamp defined in claim 18 wherein  
2      said lamp head comprises a plate, a plurality of light-emitting  
3      diodes mounted on said plate and a spiral contact spring  
4      resiliently engageable with a battery in said shaft.

1                   20. The bar-shaped lamp defined in claim 19 wherein  
2    said foot member has a portion between said spike and said tool  
3    which is flush with said shaft and adapted to be inserted into  
4    said shaft.